



SPARK PLUG TYPES BY HEAT RANGE

Thread Size	Heat Range	Standard Types	Resistor Types (with suppressor)
14mm Reach 3/4" (19mm) Projected Core Nose	Hot ↑ ↓ Cold	N-16Y	RN-16Y
		N-14Y	RN-14Y
		N-13Y	
		N-12Y	RN-12Y
		N-11Y	RN-11Y
		N-10Y	RN-10Y
		N-9Y	RN-9Y
		N-8Y	
14mm Reach .472" (12mm) Projected Core Nose	Hot ↑ ↓ Cold	N-7Y	RN-7Y
		N-6Y	
		L-95Y	
		L-92Y	
		L-87Y	RL-87Y
		L-82Y	
		L-81Y	

ROVER

1953-58: 60, 75, 80, 90

95, 100, 105, 105R, 105S, 3 Litre

* For fouling

110

2000 single carb

2000 twin carb

3.5 Litre V8 up to 1972

3.5 Litre V8 1972 on

3.5S

Three thousand five

Land Rover to 1954

1954 on: 4 cyl. 7:1cr

8:1cr

Land Rover 6 cyl.

Range Rover to 1972

Range Rover 1972-1977

1977 on 3.5 V8

2.25 Litre W/EEC

N-8 0.7

N-5* 0.7

N-12Y 0.7

N-4 0.6

N-9Y 0.6

N-7Y 0.6

L-87Y 0.6

L-92Y 0.6

L-92Y 0.6

L-87Y 0.6

N-8 0.5

N-8 0.7

N-12Y 0.7

N-5 0.7

L-87Y 0.7

L-92Y 0.7

N-12Y 0.7

N-12Y 0.8